



Delta

Petrol



DT12140PHR

**12
Lpm**

**140
Bar**

**2030
Psi**

**Petrol
Honda**

Petrol

Delta - DT12140PHR



POWERED by
HONDA

12 **140**
Lpm **Bar**



The Delta petrol engine driven pressure washer is highly versatile & suitable for a wide range of heavy-duty industrial and commercial cleaning applications.

For longevity the Delta is powered by an ultra reliable Honda engine, fitted with a 2:1 gearbox & 1450 Rpm Interpump plunger pump - an outstanding combination of high performance & reliability.



**Honda GX160
Engine**



**Interpump
44 Series**

| General | |
|--------------------|--|
| Weight | 43Kg |
| Dimensions | L910 - W565 - H890 mm |
| Noise level | LWA 111dB |
| HP hose | 10m single wire 3/8" id |
| Suction hose | 3m with 50 mesh weighted filter |
| Gun & lance | Gun with extension + twin lance ext |
| Nozzles | 1 high pressure - 1 low pressure |
| Chemical injection | Low-pressure chemical injector |
| Trolley | Powder coated steel - 10" pneumatic wheels |

| Pump | |
|------------------|-------------------------------------|
| Make | Interpump |
| Model | W140M |
| Flow | 12 Lpm |
| Pressure | 140 Bar - 2030 Psi |
| Lubrication | Oil splash |
| Materials | Ceramic plungers & brass manifold |
| Speed | 1450 Rpm |
| Drive | Via 2.2:1 reduction gearbox |
| Pressure control | Controlset with adjustable pressure |
| By-pass system | Internal recirculation |

| Engine | |
|---------------|----------------------------------|
| Make | Honda |
| Model | GX160 |
| Power | 5.5Hp - Gross / 4.8Hp - Net* |
| Fuel capacity | 3.6 Litres |
| Lubrication | Oil splash |
| Oil alert | Low level engine shutdown system |
| Cooling | Air cooled |
| Fuel system | Carburettor |
| Starting | Recoil |
| Ignition | Transistorised pointless |

*Net power @ 3600 Rpm in accordance with SAE J1349